



HD15002E1C

HD Series – Pressure Steamer

Keeping Idaho Clean and Green

Steam / Hot / Cold Water – Diesel Heated, Electric Motor

The **HD Series** offers rugged, dependable, affordable service. It features a heavy-duty stainless steel frame with pneumatic wheel kits standard, handles, panels and coil protection – offering lifetime corrosion resistance. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives for optimal cleaning effectiveness. High efficiency dual pass coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

PRESSURE	1500psi
FLOW CAPACITY	2.0gpm
OUTLET TEMP	Adjustable to 250°F (140 °F rise)
POWER/ENGINE	2.0 hp ©Instant Trigger Start
VOLTS/PHASE/AMPS	115v / 1ph / 20a
POWER CORD	35' cord with Ground Fault Circuit Interrupter for additional safety
CONTROLS/SWITCHES	Lighted rocker switches, adjustable thermostat
PUMP	CAT pump, Triplex Ceramic Plunger w/ Oil Bath, Brass head, Stainless steel valves
POWER DRIVE	Direct Drive
PRESSURE CONTROL	Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc
WATER SUPPLY	Pressure Fed
PRESSURE HOSE	3/8" x 50' Steel Wire Braid Hose, 3000 psi, 250°F Rated
GUN/WAND	Insulated Shut Off Gun / 36" Wand w/ Nozzle Quick Connector
SOAP INJECTION	Downstream soap/chemical injection, activated with soap nozzle
NOZZLE	#3.0(15°) #2.5(25°) #65(40° Soap)
BURNER COIL	½" Sch 80 Coil, Stainless Steel Coil Enclosure, Dual Pass, High Efficiency
BURNER/POWER	Beckett Oil Fired, Automatic Ignition, Forced Draft, Inline fuel filter
BURNER FUEL/CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity, up to 8hrs. run time
FRAME CONSTRUCTION	Stainless steel frame, coil wrap, and panels
WHEELS	4) 10" foam filled wheels installed
WEIGHT/DIMENSION	249#, 47x29x36

*Specifications subject to change without notification and may vary due to ambient conditions.



Featuring:

- ✓ **High Efficiency Heater** – Unique Dual Pass coil, with double wall stainless steel insulation, capture heat on both sides of the Schedule 80 pipe to burn less fuel.
- ✓ **Compact and Portable** – Wheels included. Easily moved to wherever you need to clean
- ✓ **Automatic Startup and Shut down** – E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage

Options...

Stainless Steel Hose Reel (AR003)



208-459-3645 fax

208-459-3464 phone

Email sales@vikingindustrial.com

www.vikingindustrialsystems.com